



KEACO LLC  
 1006 ASSEMBLY CIRCLE  
 SCHERTZ, TX 78154

TEL: (210) 651-6688  
 FAX: (210) 651-9020

# TECHNICAL DATA SHEET

## KEAPAK™ KP-200SS PSA COVER TAPE

### FOR POLYSTYRENE OR POLYCARBONATE CARRIER TAPE

**Description:** A pressure sensitive adhesive based Cover Tape for use when antistatic properties are required.

**Benefits:**

- Easy to use and seals exceptionally well
- Performs within EIA 481 bonding requirements
- Bonds to polystyrene and polycarbonate carrier tapes
- Re-sealable with super smooth peel back

<u>Properties</u>	<u>Value</u>	<u>Test Method</u>
Min. Break Strength:	20-90 gf	Q/321282GRT (01-2013)
Overall Thickness:	.00236" (0.06 +/- 0.003mm)	ASTM D374
Elongation:	≥ 20%.	GB/T7753
Overall Width Tolerance:	+/-0.10mm (9.3mm – 97.5mm)	Laser Micrometer
Surface Resistivity:	10 <sup>6-9</sup> ohms / square	ASTM D257
Transparency:	≥72%	Q/321282GJQ02
Tensile Strength:	40 KN/m	GB/T7753
Aging Data:	50 gf	Q/321282GJQ02

**Storage Conditions:** Store in a dry and sealed condition. Avoid direct sun light and moisture. Not to exceed 105 ° F (40°C).

**KEAPAK™** KP-200SS PSA Cover Tape should be stored in a controlled environment. The optimum storage conditions defined above will yield a shelf life of 12 months from the date of manufacturing.

01/01/19

The information above is based on our experience to date and we believe it to be reliable. It is intended only as a guide for use at your discretion and risk. We assume no liability in connection with the use of the product described above. None of the information herein shall be taken as a license to operate under, or a recommendation to infringe, any patents. KEACO LLC makes no warranty, expressed or implied, as to the suitability of these materials for any specific use.