



KEACO LLC
 1006 ASSEMBLY CIRCLE
 SCHERTZ, TX 78154

TEL: (210) 651-6688
 FAX: (210) 651-9020

TECHNICAL DATA SHEET

CCD/KEACO™ ONE-PIECE SMD REELS

CCD/KEACO™ SMD Reels feature a sturdy one-piece polystyrene construction with no assembly required. All CCD/KEACO™ SMD reels are externally antistatic and meet current EIA-481 standards.

Properties	Material / Test Method	Value
Material:	High Impact Polystyrene	
Surface Resistivity (ASTM D-257 at 12% RH):		≤10 ⁹ ohms / square
Static Decay (EIA-541 Method 4046 of standard 101C at 12% RH):		100% discharge in .05 sec.
Shelf Life:	36 months	
Color:	White	

Reel Sizes	Hub Diameter / Type	Reels / Box	Weight / Box (lbs)
7" x 8mm	60mm / Round	144	19
7" x 12mm	60mm / Round	108	17
7" x 16mm	60mm / Round	96	15
7" x 24mm	60mm / Round	72	13
13" x 8mm	60mm / Round	52	32
13" x 8mm	100mm / Round	40	26
13" x 12mm	60mm / Round	33	20
13" x 12mm	100mm / Round	33	20

1/01/2019

The information above is based on our experience to date and we believe it to be reliable. It is intended only as a guide for use at your discretion and risk. We assume no liability in connection with the use of the product described above. None of the information herein shall be taken as a license to operate under, or a recommendation to infringe, any patents. KEACO LLC makes no warranty, expressed or implied, as to the suitability of these materials for any specific use.